

NB-839



220-240V AC Mains Power Photoelectric Smoke Alarm with 9V DC Battery back-up

Under VdS approval - EN 14604:2005

Features

- 220Vac - 240Vac 50Hz , 35mA
- Photoelectric sensing technology
- 9V Carbon Zinc or Alkaline back up battery included
- Inter-connectable up to 38 units over a maximum of 250m
- Alarm indication: 85 dB at 3 m
- Low battery audible indication
- Hush/Silence button
- Built-in test facility button
- Green LED indicates " power on"
- Alarm will not operate without battery
- Easy fit, surface mount base design.
- Complies with VDS standard and EN 14604:2005
- Five-year limited warranty

Model

Model	AC 220V	Battery backup	AC hardware connector	Interconnection function	Relay output	Vds approval under PrEN 14604	CE Approval
NB839	●	●	○	●	○	●	○

Specs

Main Power Source	220 - 240VAC, 50Hz
Secondary Power Source	9VDC Carbon Zinc or Alkaline Battery
Operating Current (Max)	35mA
Operating Temperature	0°C to 45°C
Ambient Humidity	10% to 90%
Interconnecting	38 Alarms over 250 meters maximum
Horn Level	85dB at 3 meters minimum
Complies with	EN 14604-2005
Diameter	127mm
Height	45mm

